

Answer 1

HTML (index.html)

<!DOCTYPE html>

<html lang="en">

<head>

 <meta charset="UTF-8">

 <meta name="viewport" content="width=device-width, initial-scale=1.0">

 <title>Layout with Div</title>

 <link rel="stylesheet" href="style.css">

</head>

<body>

 <div class="container">

 <div class="header">Header</div>

 <div class="navigation">Navigation</div>

 <div class="content">Content</div>

 <div class="sidebar">Sidebar</div>

 <div class="footer">Footer</div>

 </div>

</body>

</html>

CSS (styles.css)

* {

 margin: 0;

 padding: 0;

 box-sizing: border-box;

}

.Container {

display: grid;

grid-template-areas:

"header header header";

"Navigation Content Sidebar";

"footer footer footer";

grid-template-columns: 200px 1fr

grid-template-rows: 80px 1fr 60px

height: 100vh;

gap: 10px;

}

.header {

grid-area: header;

background-color: #4CAF50;

color: white;

text-align: center;

padding: 20px;

}

.navigation {

grid-area: navigation;

background-color: #2196F3;

color: white;

padding: 20px;

}

Answer: 2

```
<table border="1">
```

```
<tr>
```

```
<th> h1 </th>
```

```
<th> h2 </th>
```

```
<th> h3 </th>
```

```
</tr>
```

```
<tr>
```

```
<td> c1 </td>
```

```
<td> c2 </td>
```

```
<td> c3 </td>
```

```
</tr>
```

```
<tr>
```

```
<td> </td>
```

```
<td> c3 </td>
```

```
<td> c4 </td>
```

```
</tr>
```

```
</table>
```

Part - 2

Answer: 4

```
<?php
```

```
for ($i=5; $i<=15; $i++) {
```

```
echo $i. "<br>";
```

```
}
```

Answer : 4.

let km = Prompt ("Enter value in kilometers: ");

let cm = km * 100000; // 1 km = 100000 cm

alert (km + "kilometers" + " " + cm + "centimeters");