

Solutions

Solution1

```
#include <stdio.h>
void main() {
    printf("\n Dr Sheelesh Kumar Sharma"); // it displays the string inside quotation on
computer screen
    printf("\n IMS Ghaziabad"); // it displays the string inside quotation on computer screen
}
```

Output

```
Dr Sheelesh Kumar Sharma
IMS Ghaziabad
```

Solution2

```
#include <stdio.h>
void main() {
    int n1, n2, sum; // it declares three variables n1, n2 and sum as integer type

    printf("Enter two integer numbers: ");
    scanf("%d %d", &n1, &n2); // it reads two numbers that are stored in variables n1 and n2
respectively

    sum = n1 + n2; // calculating sum

    printf("sum = %d",sum); //it displays the value of sum
}
```

Output

```
Enter two integer numbers: 10 20
Sum = 30
```

Solution3

```
#include <stdio.h>
void main() {
```

```
int x;
```

```
x= 20/(8-4)*8-2;
```

```
printf("x = %d",x); //it displays the value of x  
}
```

Output

x = 38

Solution4

```
#include <stdio.h>  
void main() {  
    int dividend, divisor, quotient, remainder; // it declares variables as integer type  
    printf("Enter dividend: ");  
    scanf("%d", &dividend); // it reads the value of dividend  
    printf("Enter divisor: ");  
    scanf("%d", &divisor); // it reads the value of divisor  
  
    quotient = dividend / divisor; //it computes quotient  
  
    remainder = dividend % divisor; // it computes remainder  
  
    printf("Quotient = %d\n", quotient); // it displays the value of quotient  
    printf("Remainder = %d", remainder); // it displays the value of remainder  
}
```

Output

Enter dividend: 20
Enter divisor: 3
Quotient = 6
Remainder = 2

Solution 5

Swap numbers using temporary variable

```
#include<stdio.h>  
void main() {  
    int n1, n2, temp;
```

```

n1=10;
n2=20;

temp = n1; // Value of n1 is assigned to temp
n1 = n2;   // Value of n2 is assigned to n1
n2=temp;   // Value of temp (initial value of n1) is assigned to n2

printf("\n After swapping, n1 Number = %d", n1);
printf("\n After swapping, n2 Number = %d", n2);
}

```

Output

After swapping, n1 Number = 20
 After swapping, n2 Number = 10

In the above program, the temp variable is assigned the value of the n1 variable. Then, the value of the n1 variable is assigned to the n2 variable. Finally, the temp (which holds the initial value of n1) is assigned to n2. This completes the swapping process.

Swap numbers without using temporary variables

```

#include<stdio.h>
void main() {
    int n1, n2;
    n1=40;
    n2=10;

    // Swapping
    n1 = n1 - n2; // n1 = 40-10 so n1= 30
    n2 = n1 + n2; // n2 = 30+10 so n2= 40
    n1 = n2 - n1; // n1 = 40-30 so n1=10
    printf("\n After swapping, n1 Number = %d", n1);
    printf("\n After swapping, n2 Number = %d", n2);
}

```

Output

After swapping, n1 Number = 10
 After swapping, n2 Number = 40`

Solution 6

```
#include <stdio.h>
void main(){
    int n1, n2, n3, largest;
    printf("Enter three different numbers: ");
    scanf("%d %d %d", &n1, &n2, &n3);

    if (n1 > n2 )
        largest = n1;
    else
        largest = n2;
    if (n3 >= largest)
        largest=n3;

    printf("Largest number is %d", largest);
}
```

Output

```
Enter three numbers: 30 20 40
Largest number is 40
```

Solution 7

```
#include <stdio.h>
void main() {
    int num;
    printf("Enter a number: ");
    scanf("%d", &num);
    if ((num % 2) == 0) {
        printf("Even number");
    }
    else
        printf("Odd number");
}
```

Output 1

```
Enter a number: 12
Even number
```

Output 2

```
Enter a number: 11
```

Odd number

Solution 8

```
#include <stdio.h>
void main() {
    int n, i;
    printf("Enter an integer: ");
    scanf("%d", &n);
    for(i = 1; i <= 10; ++i) {
        printf("%d * %d = %d \n", n, i, n * i);
    }
}
```

Output

```
Enter an integer: 9
9 * 1 = 9
9 * 2 = 18
9 * 3 = 27
9 * 4 = 36
9 * 5 = 45
9 * 6 = 54
9 * 7 = 63
9 * 8 = 72
9 * 9 = 81
9 * 10 = 90
```

Solution 9

The Fibonacci sequence: 0, 1, 1, 2, 3, 5, 8, 13, 21, 34

The Fibonacci sequence is a sequence where the next term is the sum of the previous two terms.

The first two terms of the Fibonacci sequence are 0 followed by 1.

```
#include <stdio.h>
void main() {
    int i, n, t1 = 0, t2 = 1, nextTerm;
    printf("Enter the number of terms: ");
    scanf("%d", &n);
    printf("Fibonacci Series: ");
```

```

for (i = 1; i <= n; ++i) {
    printf("%d, ", t1);
    nextTerm = t1 + t2;
    t1 = t2;
    t2 = nextTerm;
}
}

```

Output

Enter the number of terms: 10
 Fibonacci Series: 0, 1, 1, 2, 3, 5, 8, 13, 21, 34,

Solution 10

```

#include <stdio.h>
void main() {
    int n, sum = 0, digit;
    printf("Enter an integer: ");
    scanf("%d", &n);
    while (n != 0) {
        digit = n % 10;
        sum = sum + digit;
        n = n / 10;
    }
    printf("Sum of the digits = %d", sum);
}

```

Output

Enter an integer: 142
 Sum of the digits = 7

This program takes an integer input from the user 142. The While loop is used until $n \neq 0$ is false. In each iteration of the loop, each digit (using $\text{digit} = n \% 10$) when n is divided by 10 is calculated and the value of n is reduced by 10 times ($n = n / 10$). Inside the loop, the sum of digits of an integer number is computed using $\text{sum} = \text{sum} + \text{digit}$.

Solution 11

```

#include <stdio.h>
void main() {

```