

DATA COMMUNICATION ASSIGNMENT.

①. Types of Network.

- * ~~LAN~~ LAN
- * WLAN
- * WAN

LAN (Local area Network)

* A local Area network is usually privately owned and links the device in a single office, building, or campus.

* Currently, LAN size is limited to a few kbps

* LANs are designed to allow resources to be shared between personal computer or workstation.

* The resource to be shared can include hardware, software or data.

* Software can be stored on this central server and used as needed by the whole group.

* The most common LAN topologies are ring and star.

* Ethernet (IEEE 802-3) is one example of LAN.

WLAN - (Wireless LAN)

* IEEE has defined the specification for a wireless LAN called IEEE 802-11, which covers the physical and data link layers.

* A BSS without any AP is called an ad hoc network, a BSS with an AP is called an infrastructure network.

WAN (Wide Area Network)

* A wide area network provides long distance transmission of data, image, audio, and video information over large geographic areas that may comprise a country, a continent, or even the whole world.

①

- * A WAN can be as complex as the backbones that connected the internet or as simple as a dial up line that connects a home computer to the internet.

- * The Switched WAN connects the and system, which usually comprises a router that connects to another LAN or WAN

2. SHIELDED TWISTED PAIR (STP)

- * Shielded twisted pair (STP) is a special kind of copper telephone and local area network (LAN) wiring used in some business installations

- * Twisted pair is the ^{old} ~~ordinary~~ copper wire that connects many computer networks

- * To reduce cross talk or electromagnetic induction between pairs of wires two insulated upper wires are twisted around each other.

UNSHIELD TWISTED PAIR (UTP):-

- * UTP cables are mostly used for LAN Networks
- * They can be used for voice, low-speed data, high-speed data, audio and paging Statement System and building automation and control System.
- * UTP cable can be used in both the horizontal and backbone cabling subsystem
- * UTP is a ubiquitous type of copper cabling used in telephone wiring in and LANs.

3. Base band and Broadband Transmission. 3

BASEBAND Transmission

- * Baseband ~~transmission~~ ^{technology} uses digital signals in data transmission
- * It sends binary values directly as pulsed at different voltage levels
- * Baseband supports bidirectional communication
- * baseband technology is mainly used in ethernet networks to exchange data between nodes
- * uses coaxial, twisted pair and fiber optic cables

Broadband Transmission.

- * broadband ~~technology~~ uses analog signals in data transmission
- * It uses a special analog wave known as the carrier wave
- * broadband supports only unidirectional communication
- * broadband is typically used in an environment that transmits audio, video and data simultaneously
- * use radio waves, coaxial cables and fiber optic cables.

6

HUB	MODERN	ROUTER	SWITCH
The passive hub commands the wires coming from different branches	A modern modulator and demodulator electronic Signal sent through physical lines Coaxial cables	Routers are conceptually similar to bridges except that they are found in the network layer	When we use the term switch we must be careful because a switch can mean two different things.
Active hubs or multipoint repeaters operate only at the physical layer	A modern modulator one or more carrier waves signals to encode digital information.	A router is a layer-3 device that routes packets based on their logical addresses	A ^{Switch} L2 switch is a bridge and performs up to data link layer.
Passive hubs redirect the traffic on the connected machines	A modem can be used with almost any means of transmission analog signals	The routing ^{routing} latter are normally dynamic and are updated using routing protocols.	A L3 switch and router is synonymous and more sophisticated

5. MORE THE NIC cards FROM ONE PC TO another PC. does the MAC address get transferred.

* Yes, that's because MAC addresses are hard wired into the NIC circuitry not the PC

* This also means that a PC can have a different MAC address when another one replaced the NIC card

* NIC is short for Network Interface card

* MAC stands for Media Access Control

6 When Troubleshooting computer network problem what common hardware related problems can occur?

* A large percentage of a Network is made up of hardware.

* Problems is there areas can range from malfunctioning hard driver broken NICs and even hardware startups.

8.

* Incorrect hardware configuration is also one of these culprits to look into.

7. Where is the best place to install an Anti-virus program?

* An Anti-virus program must be installed on all server and workstation to ensure protection

* That's because individual users can access any workstation and introduce a computer virus.

* You can plug in this removable hard drives or flash drives.

* An anti-virus program is installed in the best place.

8. Static IP

(9)

* A static IP is an IP address that always stays the same

A static IP address is usually more expensive than a dynamic IP address and some ISPs do not supply a static IP address.

Dynamic IP

* A dynamic IP is an IP address that an ISP lets you use temporarily.

Dynamic IP addresses are assigned using either DHCP or PPPoE

Difference between IPv4 & IPv6

IPv4	IPv6
IPv4 is 32 bit binary number	IPv6 is 128 bit binary number
IPv4 addresses are separated by periods	IPv6 addresses separated by colons
unicast, broadcast and multicast is type of address	unicast, multicast and anycast is type of address

9. ICP/IP MODEL:-

(10)

* The Internet protocol Suite, commonly known as TCP/IP, is the set of communications, protocols used in the Internet and computer networks.

* The current foundational protocols in the suite are the transmission control protocol (TCP) and the internet protocol. (IP)

Layers:-

1. Application Layer
2. Network Interface Layer
3. Transport Layer
4. Internet Layer

Application Layer :-

* The transport layer establishes basic data channels the application users of task specific data - exchange.

Internet Layer:-

(11)

* The Internet Layer provides an Unreliable datagram transmission facility.

Network Interface Layer

* A network layer is a combination of the data link and defined in the article of OSI reference model.

10. Web BROWSER

* A web browser is computer software application that functions at the application layers of an open system interconnection model and allow users to access the internet.

* A web browser is application software for accessing the world wide web.

Examples :-

(12)

- * Google chrome
- * Mozilla firefox
- * Apple Safari
- * Microsoft edge
- * Opera
- * Internet Explorer

11. Search engine

* A search engine is a software program that helps people find the information they are looking for online using keywords or phrases

* search engine are able to return results quickly - even with millions of websites online - by scanning the internet continuously and indexing every page they find.

Examples:-

Google, Bing, Yahoo!, Baidu, AOL, DuckDuckGo and MSN search

12. Internet.

* The Internet is a global network of connecting millions of users world wide via many computers networks using a simple standard common addressing system and basic communication protocol called TCP/IP

* Its evolution depends on rough consensus about technical proposals and no running code.

WWW

* WWW stands for world wide web

* The world wide web is the universe of networks accessible information

* WWW can be defined as "All resources and users on the Internet that are using the HTTP

Uses of Internet in Daily Life

(14)

- * Education
- * Shopping
- * Research and development
- * Digital Transaction
- * Money management

13. Internet Service Provider :-

* An Internet Service Provider (ISP) is an organization that provides services for accessing, using, or participating in the internet.

Internet service typically provided by ISPs include internet access, Internet transit, domain name registration, web hosting and Usenet services.

Example :-

BSNL, Airtel, Jio and Vodafone.

MAC Address	IP Address	Port Address
MAC stands for Media access control	IP stands for Internet Protocol	Ports are ranging from 0 to 65535
It consists of a 48-bit address	It consists of a 32-bit address	It consists of a 16-bit address
It is referred to as a physical address	It referred to as a logical address	Port is address of system.
It works at the link layers of the OSI model	It works at the network layer of OSI model	Port address of the particular service on the particular system.
Dashes are not used in MAC address	In IP, IPV4 users ABCD and classes	Port address used for remote access

(15)

15. VIEW MY Internet browser's history:-

1. Open Google Chrome
2. Click: This option is in the top-right corner
3. Select history
4. Click history:- It's at the top of the pop-out menu
5. Review your browsing history.